



ECLIPS
inventive engineering

Flatrack ISO 1C

NSN - 3990-66-162-4395
Flatrack ISO 1C



PRODUCT FEATURES

- > Folding A-Frame for vertical stacking for transport and storage
- > Payload capacity 13,100 kg @ 2.5 x gravity
- > 22 side tie-downs, 11 per side, rated at 4536 kg each
- > 4 large tie-downs, rated at 6550 kg each
- > Laden and unladen forklift pockets
- > Container Interfaces:
 - ISO 1C - can accommodate one
 - 2/3 ISO - can accommodate one + one Tricon
 - ISO 1D - can accommodate two
 - Tricon (1/3 ISO) - can accommodate three
- > Fully verified against Army Standard DEF(AUST)8152, STANAG 2413 compliant, CSC certified, MILS(STD)209 compliant tie-downs, certified for use with Australian Army MAN ILHS vehicle
- > Full System Safety program - deemed safe SFAIRP
- > Over 2000 in service with the ADF and NZDF
- > Options: cargo gate kit, shipping legs, specialist adaptor platforms.



SBI-101543_v2-0

SPECIFICATIONS

	Length	Width	Height
mm	6058	2438	300 (platform height)
ft in	20' 0"	8' 0"	1' 0"

	Tare Weight	Maximum Payload	Maximum Gross Weight	Stacking Limit (CSC compliance)
kg	2100	13,100	15,200	27,300
lb	4629	28,880	33,510	60,186

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS



WWW.ECLIPS.ENGINEERING

P: 1300 ECLIPS
E: info@eclips.engineering